



MS-900 SELF-ADHESIVE ARROW TAPE

Technical Data



Description

MS-900 self-adhesive arrow tape is constructed using a premium grade thermoplastic film with an aggressive acrylic pressure-sensitive adhesive. They are used to provide information regarding direction of flow of pipe's contents. All arrow tape conforms to the ASME A13.1-2015 Scheme for the Identification of Piping Systems and ANSI Z535-2017 with regard to arrow size and width of tape. Recommend MS-1000 UV Overlamine for outdoor use.

Physical and Chemical Characteristics

Base Material:	Premium-grade Thermoplastic
Material Thickness:	.004" (.1 mm)
Service Temperature:	-50°F to 180°F (-45°C to 82°C)
Application Temperature:	+50°F (10°C)
Chemical Resistance:	Good
Water Resistance:	Excellent
Expected Outdoor Durability:	Indoor Use Only
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	n/a
Text Height:	n/a
Typical Sizes:	1" x 30 YDS 2" x 30 YDS 4" x 30 YDS
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)
Options:	Custom Sizes Available
Chemical Table	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 11/24/2021



MS-900 SELF-ADHESIVE ARROW TAPE

Technical Data

Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Fire quenching liquids	White text on red	Sample
Toxic and corrosive fluids	Black text on orange	Sample
Flammable fluids	Black text on yellow	Sample
Combustible fluids	White text on brown	Sample
Potable, cooling, boiler feed and other water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on gray	Sample
Defined by user	White text on black	Sample

Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
Materials Inherently Hazardous		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
Materials Inherently Low Hazard		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
Fire Quenching Materials		
Water, Foam, CO ₂ , Halon, etc.	White text on red	Sample