



MS-900 SELF-ADHESIVE CONDUIT AND CABLE MARKERS

Technical Data

110 VOLTS

120 VOLTS

Description

MS-900 self-adhesive conduit and cable are made of a premium grade .004" thick flexible thermoplastic film coated with a permanent acrylic pressure sensitive adhesive. Use MS-900 adhesive labels to identify a plant's electrical services and equipment.

- Designed for labeling conduit, panel boxes, circuit breakers and connections to equipment
- Black text on orange labels provides a highly visible warning of potential electrical hazards
- Custom legends and other color combinations are available

Physical and Chemical Characteristics

Base Material:	Premium-grade Thermoplastic
Material Thickness:	.004" (.1 mm)
Service Temperature:	-50°F to 180°F (-45°C to 82°C)
Application Temperature:	+50°F (10°C)
Chemical Resistance:	Good
Water Resistance:	Excellent
Expected Outdoor Durability:	Indoor Use Only
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	n/a
Text Height:	Customizable
Typical Sizes:	Customizable
Standard Colors:	Black text on orange label
Options:	Customizable legends & Colors available
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 11/23/2021