



# SUBSEA HDPE MARKERS

## Technical Data

### Description

The MSC subsea marker is made from two color, co-extruded HDPE. The material is manufactured by extruding one color on the inside and a contrasting color on the outside. The layers are combined while the material is still molten. The material will not delaminate, nor will it absorb water. It will not swell, crack, chip, dent, or rot. The legend is engraved into the surface, creating a high contrast, easily readable marker. The material has the ability to be engraved on both sides, giving it greater range of visibility. It is also UV stabilized for applications above water. Various color combinations are available.



### Physical and Chemical Characteristics

<b>Standard Material:</b>	Co-extruded HDPE
<b>Standard Thickness:</b>	1/2" (12.5 mm) nominal
<b>Service Temperature:</b>	-100°F to 180°F (-73°C to 82°C)
<b>Standard Colors:</b> (Non-standard colors available upon request)	Engraved black text, yellow foreground
<b>Mounting:</b>	Std 1/4" (6.35 mm) holes, 2 places
<b>Finish:</b>	Smooth pebble finish with rounded corners
<b>Text Height:</b>	Sized to fit within tag boundary or comply with specified height

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Revised on 10/24/2019

3902 81 Avenue Leduc, AB T9E 0C3

Ph: 844.986.8480 | Email: mscsales@markserv.com | Website: www.markservcanada.ca