## MS-478 SELF-ADHESIVE PIPE MARKERS AND LABELS

**Technical Data** 





#### Description

MS-478 self-adhesive pipe markers and labels are manufactured from premium grade polyester with a permanent pressure-sensitive acrylic adhesive. They are used to provide line service designations, system color-coding or various labeling needs. Flow directional arrow tape or individual arrow markers are used with pipe markers to indicate direction of flow. MS-478 markers are available in a variety of standard and custom colors. To extend service life, optional MS-1000 over-lamination may be added MS-478 contains no PVC (Polyvinyl Chloride).

# **Physical and Chemical Characteristics**

Base Material:	Premium-grade Polyester		
Material Thickness:	.002" (.051 mm)		
Service Temperature:	-50°F to 250°F (-45°C to 121°C)		
<b>Application Temperature:</b>	+32°F (0°C)		
<b>Chemical Resistance:</b>	Good		
Water Resistance:	Excellent		
<b>Expected Outdoor Durability:</b>	Indoor Use Only		
Storage Durability:	Up to 2 Years		
Abrasion Resistance:	Good		
Mounting:	Permanent pressure sensitive acrylic adhesive backing		
Finish:	Semi-Gloss Semi-Gloss		
Text Height:	Designed to meet ANSI & ASME Standards (See chart)		
Typical Sizes:	Designed to meet ANSI & ASME Standards (See chart)		
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)		
Options:	Custom Sizes Available		
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good		

#### <u>Label Sizes and Letter Heights</u>

Marker Size	Pipe Diameter (Including insulation)	Marker Style	Color Field	Letter Height
1" x 8"	3/4" – 2-1/4"	А	8" long	3/4"
2-1/4" x 13"	2-1/2" – 7-7/8"	В	13" long	1-3/4"
4" x 24"	8" – 10"	С	24" long	2-1/2"
4" x 32"	Over 10"	D	32" long	3-1/2"

<sup>\*</sup>Individual arrow markers are the same width and one-half the length of the pipe markers.

# MS-478 SELF-ADHESIVE PIPE MARKERS AND LABELS

**Technical Data** 

## Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards					
Classification	Color Scheme				
Defined Applications					
Fire quenching liquids	White text on red	Sample			
Toxic and corrosive fluids	Black text on orange	Sample			
Flammable fluids	Black text on yellow	Sample			
Combustible fluids	White text on brown	Sample			
Potable, cooling, boiler feed and other water	White text on green	Sample			
Compressed air	White text on blue	Sample			
Undefined Applications					
Defined by user	White text on purple	Sample			
Defined by user	Black text on white	Sample			
Defined by user	White text on gray	Sample			
Defined by user	White text on black	Sample			

# Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards					
Classification	Color Scheme				
Materials Inherently Hazardous					
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample			
Materials Inherently Low Hazard					
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample			
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample			
Fire Quenching Materials					
Water, Foam, CO2, Halon, etc.	White text on red	Sample			

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 5/23/2022