



MS-478 SELF-ADHESIVE PIPE MARKERS AND LABELS W/ UV OVERLAMINATE Technical Data

CONDENSATE DRAIN

FUEL OIL RETURN

Description

MS-478 UV self-adhesive pipe markers and labels are manufactured from premium grade polyester with a permanent pressure-sensitive acrylic adhesive. They are used to provide line service designations, system color-coding or various labeling needs. Flow directional arrow tape or individual arrow markers are used with pipe markers to indicate direction of flow. MS-478 markers are available in a variety of standard and custom colors.

Physical and Chemical Characteristics

Base Material:	Premium-grade Polyester w/ UV Overlaminat
Material Thickness:	.003" (.076 mm)
Service Temperature:	-50°F to 250°F (-45°C to 121°C)
Application Temperature:	+32°F (0°C)
Chemical Resistance:	Excellent
Water Resistance:	Excellent
Expected Outdoor Durability:	Excellent (5+ Years)
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Very Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	Gloss Surface
Text Height:	Designed to meet ANSI & ASME Standards (See chart)
Typical Sizes:	Designed to meet ANSI & ASME Standards (See chart)
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)
Options:	Custom Sizes Available
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

Label Sizes and Letter Heights

Marker Size	Pipe Diameter (Including insulation)	Marker Style	Color Field	Letter Height
1" x 8"	3/4" – 2-1/4"	A	8" long	3/4"
2-1/4" x 13"	2-1/2" – 7-7/8"	B	13" long	1-3/4"
4" x 24"	8" – 10"	C	24" long	2-1/2"
4" x 32"	Over 10"	D	32" long	3-1/2"

*Individual arrow markers are the same width and one-half the length of the pipe markers



MS-478 SELF-ADHESIVE PIPE MARKERS AND LABELS W/ UV OVERLAMINATE Technical Data

Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Fire quenching liquids	White text on red	Sample
Toxic and corrosive fluids	Black text on orange	Sample
Flammable fluids	Black text on yellow	Sample
Combustible fluids	White text on brown	Sample
Potable, cooling, boiler feed and other water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on gray	Sample
Defined by user	White text on black	Sample

Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
Materials Inherently Hazardous		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
Materials Inherently Low Hazard		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
Fire Quenching Materials		
Water, Foam, CO2, Halon, etc.	White text on red	Sample

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 5/20/2022